
OVERVIEW



1. microSD card reader	6. HDMI
2. USB 3.2 Gen 2	7. USB 3.2 Gen 2
3. Kensington Nano Security Slot	8. Headphone / microphone combo jack (3.5mm)
4. Thunderbolt 4 / USB 4	9. Nano-SIM card slot *
5. Thunderbolt 4 / USB 4	

Notes:

• Ports with * are only available on selected models

PERFORMANCE

Processor

Processor Family

12th Generation Intel[®] Core™ i3 / i5 / i7 Processor

Processor**

Processor Name	Cores	Threads	Base Frequency	Max Frequency	Cache	Memory Support	Processor Graphics
Core i3- 1215U	6 (2 P-core + 4 E-core)	8	P-core 1.2GHz / E- core 0.9GHz	P-core 4.4GHz / E- core 3.3GHz	10MB	LPDDR4x- 4266	Intel UHD Graphics
Core i5- 1235U	10 (2 P-core + 8 E-core)	12	P-core 1.3GHz / E- core 0.9GHz	P-core 4.4GHz / E- core 3.3GHz	12MB	LPDDR4x- 4266	Intel Iris® Xe Graphics
Core i5- 1245U	10 (2 P-core + 8 E-core)	12	P-core 1.6GHz / E- core 1.2GHz	P-core 4.4GHz / E- core 3.3GHz	12MB	LPDDR4x- 4266	Intel Iris Xe Graphics
Core i7- 1265U	10 (2 P-core + 8 E-core)	12	P-core 1.8GHz / E- core 1.3GHz	P-core 4.8GHz / E- core 3.6GHz	12MB	LPDDR4x- 4266	Intel Iris Xe Graphics

Operating System

Operating System**

- Google Chrome OS
- Google Chrome OS (with Chrome Education Upgrade)
- Google Chrome OS (with Chrome Enterprise Upgrade)

Graphics

Graphics**

Graphics	Туре	Memory	TGP	Key Features
Intel UHD Graphics	Integrated	Shared	Share CPU TDP	DirectX® 12
Intel Iris Xe Graphics	Integrated	Shared	Share CPU TDP	DirectX 12.1

Monitor Support

Monitor Support

- Models with non-vPro: supports up to 4 independent displays (native display and 3 external monitors via HDMI[®] and USB 4)
 - \bullet HDMI supports up to 3840x2160@60Hz
 - USB 4 supports up to 5120x3200@60Hz
- Models with Intel vPro: supports up to 4 independent displays (native display and 3 external monitors via HDMI and Thunderbolt[™])
 - HDMI supports up to 3840x2160@60H
 - Thunderbolt supports up to 5120x3200@60Hz

Chipset

Chipset

Intel SoC (System on Chip) platform

Memory

Max Memory^[1]

- 4GB soldered memory, not upgradable
- 8GB soldered memory, not upgradable
- 16GB soldered memory, not upgradable

Memory Slots**

- Memory soldered to systemboard, no slots, single-channel (4GB models)
- Memory soldered to systemboard, no slots, dual-channel (8GB or 16GB models)

Memory Type

LPDDR4x-4266

Notes:

1. The max memory is based on the test results with current Lenovo® memory offerings. The system may support more memory as the technology develops.

Storage

Storage Support^{[1][2]}

- One drive, up to 256GB M.2 2242 SSD
- 64GB eMMC 5.1 on systemboard
- 128GB eMMC 5.1 on systemboard

Storage Slot

- eMMC on systemboard, no slots
- One M.2 2242 PCIe® 4.0 x4 slot

Storage Type**

Disk Type	Interface	Offering	Security
Flash Memory	eMMC 5.1	64GB / 128GB	-
M.2 2242 SSD	PCIe NVMe®, PCIe 4.0 x4	256GB	Opal2

Notes:

- 1. The storage capacity supported is based on the test results with current Lenovo storage offerings. The system may support larger storage as the technology develops.
- 2. System has one eMMC on systemboard or one M.2 2242 SSD exclusively

Removable Storage

Card Reader

MicroSD card reader

Multi-Media

Audio Chip

High Definition (HD) Audio, Realtek® ALC5682I codec

Speakers

Stereo speakers, 2W x2, optimized with Waves MaxxAudio®

Microphone

Dual array microphone

Camera

FHD 1080p, with privacy shutter, fixed focus

Battery

Battery

Integrated Li-Polymer 57Wh battery, supports Rapid Charge (charge up to 80% in 1hr) with 65W AC adapter

Battery Life^[1]

Configuration 1 (max battery life) Google Power Load Test: 11.4 hr @80nits

Alternate configuration 2 Google Power Load Test: 11.0 hr @80nits

Alternate configuration 3 Google Power Load Test: 10.8 hr @80nits

Notes:

1. Configuration 1 (max battery life): FHD (non-touch), Intel Pentium[®] 8505U, 4GB LPDDR4x, Google Chrome OS, 57Wh battery Alternate configuration 2: FHD (non-touch), Intel i5-1235U, 8GB LPDDR4x, Google Chrome OS, 57Wh battery Alternate configuration 3: FHD (touch), Intel i7-1265U, 16GB LPDDR4x, Google Chrome OS, 57Wh battery

All battery life claims are approximate maximum and based on results usingGoogle Power Load Test (PLT) battery-life benchmark tests.

Lenovo

Actual battery life will vary and depends on many factors such as product configuration, software, wireless functionality, power management settings, and screen brightness.

The maximum capacity of the battery will decrease with time, ambient temperature and use.

Power Adapter

Power Adapter**[1]

- 45W USB-C[®] (2-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 45W USB-C (3-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 65W USB-C slim (2-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 65W USB-C slim (3-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz

Notes:

1. AC adapter offerings depend on the country.

DESIGN

Display

Display**[1]

Size	Resolution	Touch	Туре	Brightness	Surface	Aspect Ratio	Contrast Ratio	Color Gamut	Viewing Angle
14.0″	FHD (1920x1080)	None	IPS	250 nits	Anti- glare	16:9	800:1	45% NTSC	170°
14.0″	FHD (1920x1080)	Multi- touch	IPS	300 nits	Anti- glare	16:9	800:1	45% NTSC	170°

Touchscreen

• OGS (One Glass Solution) multi-touch, supports 10-point touch

Non-touch

Notes:

1. California Electronic Waste Recycling Fee

In California, per state law, Lenovo charges an electronic waste recycling fee on this covered device at the time of sale of the product. For more information, go to https://www.calrecycle.ca.gov/Electronics/Consumer

Input Device

Keyboard

Chrome keyboard, 6-row, spill-resistant

Keyboard Backlight

LED backlight

UltraNav™

TrackPoint® pointing device and Mylar® surface multi-touch touchpad, 56 x 115 mm (2.24 x 4.53 inches)

Mechanical^{III}

Dimensions (WxDxH)

325.4 x 217 x 19.83 mm (12.81 x 8.54 x 0.78 inches)

Weight

Starting at 1.56 kg (3.44 lbs)

Case Color

Abyss blue

Case Material

PC + ABS (top), PC + ABS (bottom)

Notes:

1. The system dimensions and weight vary depending on configurations.

CONNECTIVITY

Network

Ethernet

No Ethernet

WLAN + Bluetooth®[1][2]

Intel Wi-Fi[®] 6E AX211, 802.11ax 2x2 Wi-Fi + Bluetooth 5.1, M.2 Card

WWAN

- Fibocom L850-GL, 4G LTE CAT9, M.2 card
- No support

SIM Card

No SIM card inbox

NFC

No support

Notes:

- 1. Bluetooth 5.2 is hardware ready but may run at a lower version due to OS limitation
- 2. 6GHz Wi-Fi 6E operation is dependent on the support of the operating system, routers/APs/Gateways that support Wi-Fi 6E, and the regional regulatory certifications & spectrum allocation.

Ports^[1]

Standard Ports

- 2x USB 3.2 Gen 2
- 1x HDMI, up to 4K/60Hz
- 1x microSD card reader
- 1x Headphone / microphone combo jack (3.5mm)

Optional Ports***

- 1x Nano-SIM card slot (WWAN support models)
- 2x Thunderbolt 4 (support data transfer, Power Delivery 3.0 and DisplayPort[™] 1.4) (vPro models)
- 2x USB 4 20Gbps (support data transfer, Power Delivery 3.0 and DisplayPort 1.4) (non-vPro models)

Notes:

- The transfer speed of following ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed. USB 2.0: 480 Mbit/s;
- USB 3.2 Gen 1 (SuperSpeed USB 5Gbps, formerly USB 3.0 / USB 3.1 Gen 1): 5 Gbit/s;
- USB 3.2 Gen 2 (SuperSpeed USB 10Gbps, formerly USB 3.1 Gen 2): 10 Gbit/s;
- USB 3.2 Gen 2x2 (SuperSpeed USB 20Gbps): 20 Gbit/s;

Thunderbolt 3/4: 40 Gbit/s

Docking

Docking

Various docking solutions supported via Thunderbolt or USB-C. For more compatible docking solutions, please visit <u>Docking for ThinkPad® C14 Gen 1 Chromebook</u>

SECURITY & PRIVACY

Security

Security Chip Google Security Chip H1

Physical Locks

Kensington[®] Nano Security Slot™, 2.5 x 6 mm

Smart Card Reader

No smart card reader

Fingerprint Reader

- Touch style fingerprint reader on power button, match-on-chip
- No fingerprint reader

BIOS Security

No support Other Security Camera privacy shutter

MANAGEABILITY

System Management

System Management

- Intel vPro Enterprise
- Non-vPro

SERVICE

Warranty

Base Warranty**[1]

- 1-year courier or carry-in service
- 1-year courier or carry-in with 2-year system board service (Korea only)
- 1-year limited onsite service

Notes:

1. More information of warranty policy, please access https://pcsupport.lenovo.com/warranty

ENVIRONMENTAL

Operating Environment

Temperature^{[1][2]}

- Operating: 5°C (41°F) to 35°C (95°F)
- Storage: 5°C (41°F) to 43°C (109°F)

Humidity

- Operating: 8% to 95% at wet-bulb temperature 23°C (73°F)
- Storage: 5% to 95% at wet-bulb temperature 27°C (81°F)

Altitude

Maximum altitude (without pressurization): 3048 m (10,000 ft)

Notes:

1. When you charge the battery, its temperature must be no lower than 10 $^{\circ}\text{C}$ (50 $^{\circ}\text{F}$).

2. When you charge the battery, its temperature must be no lower than 10°C (50°F).

CERTIFICATIONS

Green Certifications

Green Certifications

- EPEAT™ Gold
- ENERGY STAR[®] 8.0
- ErP Lot 3
- TCO Certified 9.0
- RoHS compliant

Other Certifications

Mil-Spec Test

MIL-STD-810H military test passed

PSREF

Reference

Product Specifications

Lenovo

- Feature with ** means that only one offering listed under the feature is configured on selected models.
- Feature with *** means that one or more offerings listed under the feature could be configured on selected models.
- Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not
 responsible for photographic or typographical errors. LENOVO PROVIDES THIS PUBLICATION "AS IS,"
 WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES
 OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow
 disclaimer of express or implied warranties in certain transactions, therefore this disclaimer may not apply to
 you.
- The specifications on this page may not be available in all regions, and may be changed or updated without notice.









